

## **Study Unit 10: BASICS OF PHP (FORMS)**

### **Outline**

- Parameterized Pages
- Form Basics
- Form Controls
- Processing Form data in PHP

### **Learning Outcomes of Study Unit 10**

You will learn the basic concepts query string and parameters, Form fields, text, select, text area, checkbox and Form submission and controls in PHP.

1.1: Query String & Parameters

1.2: Form Basics,

1.3: Form Controls

- input
- type: text, password, textarea, checkbox, radio

- label
- select, option

#### 1.4: Processing Form data in PHP

- Superglobal arrays

### Outline

- **1.1: Parameterized Pages**
- **Form Basics**
- **Form Controls**
- **Processing Form data in PHP**

*Web 2.0 Programming*

## Web Data

- Most interesting web pages revolve around data
  - Examples: Google, Baidu, IMDB, Digg, Facebook, YouTube, renren
  - Can take many formats: text, HTML, XML, multimedia
    - Many of them allow us to access their data
- Some even allow us to submit our own new data
- Most server-side web programs accept **parameters** that guide their execution

## Query Strings and Parameters

*URL ?name=value&name=value . . .*

- http://www.google.com/search?q=Obama  
http://example.com/student\_login.php?username=stepp&id=1234567

- Query string: a set of parameters passed from a browser to a web server
  - Often passed by placing name/value pairs at the end of a URL
  - Above, parameter **username** has value **stepp**, and **id** has value **1234567**
- PHP code on the server can examine and utilize the value of parameters
- A way for PHP code to produce different output based on values passed by the user

## Query Parameters: **\$ REQUEST**

```
$user_name = $_REQUEST["username"];
$id_number = (int) $_REQUEST["id"];
$eats_meat = FALSE;
if (isset($_REQUEST["meat"])) {
    $eats_meat = TRUE;
}
```

PHP

- `$_REQUEST["parameter name"]` returns a parameter's value as a string

- Test whether a given parameter was passed with `isset`

## Outline

- Parameterized Pages

- **1.2: Form Basics**

- Form Controls

- Processing Form data in PHP

## HTML Forms

- **form:** a group of UI controls that accepts information from the user and sends the information to a web server
  - The information is sent to the server as a **query string**

The screenshot shows a window titled "Add Comments Here" with a text input field at the top. Below it is a large text area for comments. To the right of the text area are two scroll bars. At the bottom of the window are five radio buttons labeled "Value 1" through "Value 5", with "Value 1" being selected. Below the radio buttons are five checkboxes labeled "Value 1" through "Value 5", with "Value 1" and "Value 2" checked. At the very bottom are two buttons: "Submit" and "Reset".

## HTML Form: <form>

```
<form action="destination URL">  
    form controls  
</form>
```

HTML

- Required **action** attribute gives the URL of the page that will process this form's data
- When form has been filled out and **submitted**, its data will be sent to the **action**'s URL
- One page may contain many forms if so desired

## Form Example

```
<form action="http://www.google.com/search">
  <div>
    Let's search Google:
    <input name="q" />
    <input type="submit" />
  </div>
</form>
```

HTML

Let's search Google:

submit

output

- Must wrap the form's controls in a block element such as `div`, `fieldset`, etc.

## Outline

- Parameterized Pages
- Form Basics
- **1.3: Form Controls**
- Processing Form data in PHP

```
<!-- 'q' happens to be the name of Google's required parameter -->
<input type="text" name="q" value="Colbert Report" />
<input type="submit" value="Booyah!" />
```

HTML

Colbert Report      Booyah!

output

## Form Controls: <input>

- **input** element is used to create many UI controls
  - an inline element that **MUST** be self-closed
- **name** attribute specifies name of query parameter to pass to server
- **type** can be **button**, **checkbox**, **file**, **hidden**, **password**, **radio**, **reset**, **submit**, **text**, ...
- **value** attribute specifies control's initial text

## Text Fields: <input>

```
<input type="text" size="10" maxlength="8" /> NetID <br />
<input type="password" size="16" /> Password
<input type="submit" value="Log In" />
```

HTML

NetID  
Password Log In

output

```
<textarea rows="4" cols="20">  
Type your comments here.  
</textarea>
```

HTML

Type your comments  
here.

output

- input attributes: `disabled`, `maxlength`, `readonly`, `size`, `value`
- `size` attribute controls onscreen width of text field
- `maxlength` limits how many characters user is able to type into field

## Text Boxes: <textarea>

- Initial text is placed inside `textarea` tag (optional)
- Required `rows` and `cols` attributes specify height/width in characters
- Optional `readonly` attribute means text cannot be modified

## Checkboxes: <input>

submit

*yes/no choices that can be checked and unchecked (inline)*

```
<input type="checkbox" name="lettuce" /> Lettuce
<input type="checkbox" name="tomato" checked="checked" /> Tomato
<input type="checkbox" name="pickles" /> Pickles
```

HTML

Lettuce  Tomato  Pickles 提交查询

output

- None, 1, or many checkboxes can be checked at same time
- When sent to server, any checked boxes will be sent with value on:
  - <http://ssw2p.3322.org/public/params.php?tomato=on&pickles=on>
- Use `checked="checked"` attribute in HTML to initially check the box

**Radio Buttons:** [<input>](#)

*sets of mutually exclusive choices (inline)*

```
<input type="radio" name="cc" value="visa" checked="checked" /> Visa
<input type="radio" name="cc" value="mastercard" /> MasterCard
<input type="radio" name="cc" value="amex" /> American Express
```

HTML

• Visa • MasterCard • American Express

output

- Grouped by **name** attribute (only one can be checked at a time)
- Must specify a **value** for each one or else it will be sent as value **on**

## Think of <input>

- So many types of **input**, why NOT use elements instead?
- <input type="text" ... /> → <text/> or <text></text> ● <input type="checkbox" ... /> → <checkbox ... />

- In fact, it is just a bad design decision when form was firstly designed and introduced into html in 1996, and we follow it so far...,
- Another flaw: **checked="checked"** ..., is it weird?

- Lessons:
- Reality is never, ever perfect
- **BUT** we will try our best to make it perfect

```
<label><input type="radio" name="cc" value="visa" checked="checked" /> Visa</label>
<label><input type="radio" name="cc" value="mastercard" /> MasterCard</label>
<label><input type="radio" name="cc" value="amex" /> American Express</label>
```

HTML

- Visa ● MasterCard ● American Express

**Submit**

output

## Text Labels: <label>

- Associates nearby text with control, so you can click text to activate control
- Can be used with checkboxes or radio buttons
- Either wrap the input elements or target input elements with id specified via the “**for**” attribute
- **label** element can be targeted by CSS style rules



Reasons for preferring label than text:

- **Functionality:** can be directly clicked on
- **Styling:** can be styled by CSS rules
- **Accessibility:** screen reader will read it when selected

---

## Drop-down List: <select>, <option>

*menus of choices that collapse and expand (inline)*

```
<select name="favoritecharacter">
  <option>Jerry</option>
  <option>George</option>
  <option selected="selected">Kramer</option>
  <option>Elaine</option>
</select>
```

HTML

output

- `option` element represents each choice
- `select` optional attributes: `disabled`, `multiple`, `size`
- Optional `selected` attribute sets which one is initially chosen

## Using `<select>` for Lists

```
<select name="favoritecharacter[]" size="3" multiple="multiple">
  <option>Jerry</option>
  <option>George</option>
  <option>Kramer</option>
  <option>Elaine</option>
  <option selected="selected">Newman</option>
</select>
```

HTML

Kramer  
Elaine  
Newman

select

output

- Optional `multiple` attribute allows selecting multiple items with shift- or ctrl-click

- Must declare parameter's name with [ ] if you allow multiple selections
- **option** tags can be set to be initially **selected**

## Option Groups: <optgroup> Web 2.0 Programming

```
<select name="favoritecharacter">
  <optgroup label="Major Characters">
    <option>Jerry</option>
    <option>George</option>
    <option>Kramer</option>
    <option>Elaine</option>
  </optgroup>
  <optgroup label="Minor Characters">
    <option>Newman</option>
    <option>Susan</option>
  </optgroup>
</select>
```

HTML



A screenshot of a web browser displaying a dropdown menu and a submit button. The dropdown menu is open, showing the option "Jerry". To the right of the dropdown is a blue rectangular button labeled "submit".

output

## Outline

- Parameterized Pages
- Form Basics
- Form Controls
- **1.4: Processing Form data in PHP**

# "Superglobal" Arrays

- PHP superglobal arrays (global variables) contain information about the current request, server, etc.:

Array	Description
<u><code>\$_GET</code></u> , <u><code>\$_POST</code></u>	parameters passed to GET and POST requests
<u><code>\$_REQUEST</code></u>	parameters passed to any type of request
<u><code>\$_SERVER</code></u> , <u><code>\$_ENV</code></u>	information about the web server
<u><code>\$_FILES</code></u>	files uploaded with the web request
<u><code>\$_SESSION</code></u> , <u><code>\$_COOKIE</code></u>	"cookies" used to identify the user (seen later)

- These are special kinds of arrays called associative arrays.

## **Questions For Study Session 10**

---

Now that you have completed this study unit, you can assess how well you have achieved its Learning Outcomes by answering these questions. Write your answers in your Study Diary and discuss them with your Tutor at the next Study Support Meeting or Online interactive sessions. You can also check your answers at the Self-Review Answers section which is located at the end of this Module.

1: Convert it to a PHP page on your Web server, which shows data you submitted at the top of this page.

## PHP Form Validation Example

\* required field

Name:  \*

E-mail:  \*

Website:

Comment:

Gender:  Female  Male  Other \*

**Your Input:**

## Self-Review Answers (SRA) for Study Unit 10

1: Convert it to a PHP page on your Web server, which shows data you submitted at the bottom of this page.

```
<!DOCTYPE HTML>
<html>
<head>
<style>
.error {color: #FF0000;}
</style>
</head>
<body>

<?php
// define variables and set to empty values
$nameErr = $emailErr = $genderErr = $websiteErr = "";
$name = $email = $gender = $comment = $website = "";

if ($_SERVER["REQUEST_METHOD"] == "POST") {
    if (empty($_POST["name"])) {
        $nameErr = "Name is required";
    } else {
        $name = test_input($_POST["name"]);
        // check if name only contains letters and whitespace
        if (!preg_match("/^[a-zA-Z-' ]*$/",$name)) {
            $nameErr = "Only letters and white space allowed";
        }
    }
}
```

```
if (empty($_POST["email"])) {
    $emailErr = "Email is required";
} else {
    $email = test_input($_POST["email"]);
    // check if e-mail address is well-formed
    if (!filter_var($email, FILTER_VALIDATE_EMAIL)) {
        $emailErr = "Invalid email format";
    }
}

if (empty($_POST["website"])) {
    $website = "";
} else {
    $website = test_input($_POST["website"]);
    // check if URL address syntax is valid (this regular expression also allows dashes in the URL)
    if (!preg_match("/\b(?:https?|ftp):\/\/|www\.)[-a-z0-9+&@#\/\%?=~_|!:,.;]*[-a-z0-
9+&@#\/\%?=~_|]/i", $website)) {
        $websiteErr = "Invalid URL";
    }
}

if (empty($_POST["comment"])) {
    $comment = "";
} else {
    $comment = test_input($_POST["comment"]);
}

if (empty($_POST["gender"])) {
    $genderErr = "Gender is required";
```

```
    } else {
        $gender = test_input($_POST["gender"]);
    }
}

function test_input($data) {
    $data = trim($data);
    $data = stripslashes($data);
    $data = htmlspecialchars($data);
    return $data;
}
?>

<h2>PHP Form Validation Example</h2>
<p><span class="error">* required field</span></p>
<form method="post" action=<?php echo htmlspecialchars($_SERVER["PHP_SELF"]);?>">
    Name: <input type="text" name="name" value=<?php echo $name;?>">
    <span class="error">* <?php echo $nameErr;?></span>
    <br><br>
    E-mail: <input type="text" name="email" value=<?php echo $email;?>">
    <span class="error">* <?php echo $emailErr;?></span>
    <br><br>
    Website: <input type="text" name="website" value=<?php echo $website;?>">
    <span class="error"><?php echo $websiteErr;?></span>
    <br><br>
    Comment: <textarea name="comment" rows="5" cols="40"><?php echo $comment;?></textarea>
    <br><br>
    Gender:
    <input type="radio" name="gender" <?php if (isset($gender) &&
```

```
$gender=="female") echo "checked";?> value="female">Female
    <input type="radio" name="gender" <?php if (isset($gender) &&
$gender=="male") echo "checked";?> value="male">Male
    <input type="radio" name="gender" <?php if (isset($gender) &&
$gender=="other") echo "checked";?> value="other">Other
    <span class="error">*<?php echo $genderErr;?></span>
    <br><br>
    <input type="submit" name="submit" value="Submit">
</form>

<?php
echo "<h2>Your Input:</h2>";
echo $name;
echo "<br>";
echo $email;
echo "<br>";
echo $website;
echo "<br>";
echo $comment;
echo "<br>";
echo $gender;
?>

</body>
</html>
```

## **References and Additional Reading Materials**

- PHP home page: <http://www.php.net/>
- W3Schools PHP tutorial: <http://www.w3schools.com/PHP/>